

Special Offer

ISUZU 42

£4568 inc VAT


This offer includes free delivery and upgraded Delux control panel


ISUZU 42

Technical Data Sheet

Technical Information

Engine	Isuzu 4LC1
Number of cylinders	4
Cubic capacity	1731 cm ³
Bore x stroke	77.4 x 92.0 mm
Max output	42 bhp 31.3 kW
Max torque	79 lbft @ 1800 r/min 107 Nm @ 1800 r/min
Combustion	Indirect Injection
Idle speed	850 r/min
Fuel consumption	2.4 lit/hr @ 1400 r/min
Oil capacity	6.6 litres
Dry weight	206 kg
Panel type	Intermediate
Skin tank size	10 sq ft
Oil type	API CC 15w/40
Engine alternator	70 Amp
Domestic alternator	70 Amp





Dimensions (mm)	A	B	C	D	E
Basic Panel	130	135	138	143	10
Intermediate Panel	170	135	168	143	10
Deluxe Panel	230	185	238	193	10

Isuzu 42 - Power Curve

Engine Speed (r/min)	Gross Power (Bhp)	Gross Torque (lb-ft)
1000	18	75
1500	28	80
1800	32	80
2000	35	78
2500	40	75
3000	42	72

Alternator output on the Isuzu 42

Engine Speed (r/min)	70A Aux Position (Amps)	70A Std Position (Amps)
1000	45	35
1500	60	50
2000	68	60
2500	70	65
3000	70	68

HMI reserve the right to change the specifications without notice. September 2004